



# LED Selectable Commercial Recessed Downlights

Color & Wattage Selectable Product Specifications



TCP's Selectable Commercial Recessed Downlights offer choices for color temperatures and wattages, making these adaptable for many situations.

## Reasons to choose LED Commercial Recessed Downlights from TCP

- 3 Selectable Wattages
- 3 Selectable Colors (30K/35K/41K)
- 50,000 hours life minimizes replacement and maintenance costs
- Flicker Free Design for consistent lighting
- Mounts directly to ceiling: 4, 6, 8, 10 or 12 inch
- Shatter resistant
- Matte Silver Finish & Frosted Diffuser
- Easy installation and integrated trim
- Snap clips allow for installation without a recessed can
- 85° beam angle (4"/6"/8"/10")
- 70° beam angle (12")
- Smooth, uniform dimming from 100 - 5%

## Ideal Applications

- Commercial
- Retail
- Industrial
- Healthcare

## Specifications:

Color Temperatures..... 3000K, 3500K, 4100K  
 Wattage options ..... 4" (7/9/12W), (6" (8/10/15W),  
 ..... 8" (11/15/19W), 10" (18/23/30W),  
 ..... 12" (18/23/30W)  
 Input Line Voltage ..... 120-277V  
 Input Line Frequency..... 50/60HZ  
 Dimming..... 0-10V

Lamp Life (rated)..... 50,000 hours  
 Minimum Starting Temp ..... -22F/-30C  
 Maximum Operating Temp..... 104°F/40°C  
 CRI..... 80  
 IC-rated for direct contact with insulation  
 UL approved for damp locations



## Specifications:



ITEM #	DESCRIPTION	VOLTAGE	LED WATTS	REPLACEMENT WATTS	LUMENS									LPW	CRI	MOL (inches)	DIA (inches)
					LOWEST WATTAGE			MIDDLE WATTAGE			HIGHEST WATTAGE						
					3000K	3500K	4100K	3000K	3500K	4100K	3000K	3500K	4100K				
<b>4" Selectable Commercial Recessed Downlight – 65 Watt Replacement • 50,000 Hour</b>																	
DLC4SWUZDCCT	LED 4" Comm Downlight CCT	120-277V	7/9/12	65	675	695	690	870	900	895	1150	1200	1190	LW:96.4/99.3/98.6 MW:96.7/100/99.4 HW: 95.8/100/99	80	6.14	4.96
<b>6" Selectable Commercial Recessed Downlight – 85 Watt Replacement • 50,000 Hour</b>																	
DLC6SWUZDCCT	LED 6" Comm Downlight CCT	120-277V	8/10/15	85	820	850	865	1030	1080	1095	1430	1530	1515	LW:103/106/108 MW:103/108/110 HW: 95/102/101	80	7.4	5.67
<b>8" Selectable Commercial Recessed Downlight – 85 Watt Replacement • 50,000 Hour</b>																	
DLC8SWUZDCCT	LED 8" Comm Downlight CCT	120-277V	11/15/19	85	1270	1300	1305	1720	1705	1775	2085	2150	2085	LW:115.5/118.2/119 MW:115/113.7/118.3 HW: 110/113.2/110	80	6.3	9.25
<b>10" Selectable Commercial Recessed Downlight – 100 Watt Replacement • 50,000 Hour</b>																	
DLC10SWUZDCCT	LED 10" Comm Downlight CCT	120-277V	18/23/30	100	2100	2150	2150	2590	2660	2660	3205	3330	3305	LW: 116.7/119.4/119.4 MW: 112.6/115.7/115.7 HW: 106.8/111/110.2	80	7.87	10.75
<b>12" Selectable Commercial Recessed Downlight – 125 Watt Replacement • 50,000 Hour</b>																	
DLC12SWUZDCCT	LED 12" Comm Downlight CCT	120-277V	18/23/30	125	2110	2160	2180	2650	2690	2690	3260	3380	3360	LW: 117.2/120/121.1 MW: 115.2/117/117 HW: 108.7/112.7/112	80	7.87	12.86

For the most up-to-date specs, please visit [www.tcpi.com](http://www.tcpi.com)