



# LED Recessed Downlights

**BEVELED DESIGNER LOOK • DIMMABLE • 35,000 HOURS**

For quick, easy, and affordable LED upgrades, switch to TCP's LED Downlights. TCP downlights have both E26 and direct wire options, PMMA plastic to prevent lens discoloration, and quick snap holding arms to quickly attach to a recessed can. With the new beveled look, these downlights provide smooth even light in the color temperature you need.



## LIMITLESS OPTIONS FOR THE FOLLOWING APPLICATIONS

- Commercial
- Retail
- Healthcare
- Industrial
- Residential

### FEATURES

### BENEFITS

Long life: 35,000 hours	Minimizes replacement and maintenance costs
Very low heat generation	Perfect for sensitive display lighting such as art galleries
Excellent color consistency and CRI	Enhances colors of focal point while maintaining uniformity throughout lighting installation from lamp to lamp
Durable PMMA plastic housing	Prevents discoloration
Mounts directly to recessed can: 4 or 6 inch	Easy installation and integrated trim
E26 or direct wire options	Makes for a quick install
Smooth, uniform dimming from 100 - 10%	

### SPECIFICATIONS

Color Temperatures .....	2700K, 3000K, 4100K, 5000K
Wattage options .....	11W, 12W, 16.5W
Input Line Voltage .....	120 VAC
Input Line Frequency .....	50/60HZ
Lamp Life (Rated) .....	35,000 hours
Minimum Starting Temp .....	-22F/-30C
Maximum Operating Temp .....	40°C
CRI .....	80



**5 YEAR WARRANTY**  
\* Based on 12 hours use per day

IC-rated for direct contact with insulation

UL approved for damp location (indoor only)—outdoor environment may cause yellowing of the white trim. This is not covered by warranty.



6 inch Dimmable Downlight



4 inch Dimmable Downlight



Direct Wire

E26

LED  
we know light.™





# LED Recessed Downlights

BEVELED DESIGNER LOOK • DIMMABLE • 35,000 HOURS

ITEM #	DESCRIPTION	VOLTAGE	WATTS	INCANDESCENT WATTS	LPW	LUMENS	COLOR	HOURS	CRI	MOL (inches)	DIA (inches)	BEAM ANGLE	BASE	WARRANTY YEARS
--------	-------------	---------	-------	--------------------	-----	--------	-------	-------	-----	--------------	--------------	------------	------	----------------

## LED 75W Equivalent Options

### 11W DR4 Downlight • Dimmable • 35,000 Hour

L75DR4D3527K	LED 11W DR4 DIM 2700K	120V	11	75	85.0	850	2700K	35,000	80	3.0	5	120°	E26	5
L75DR4D3530K	LED 11W DR4 DIM 3000K	120V	11	75	85.0	850	3000K	35,000	80	3.0	5	120°	E26	5
L75DR4D3541K	LED 11W DR4 DIM 4100K	120V	11	75	85.0	850	4100K	35,000	80	3.0	5	120°	E26	5
L75DR4D3550K	LED 11W DR4 DIM 5000K	120V	11	75	85.0	850	5000K	35,000	80	3.0	5	120°	E26	5

### 12W DR56 Downlight • Dimmable • 35,000 Hour

L75DR56D3527K	LED 12W DR56 DIM 2700K	120V	12	75	70.8	850	2700K	35,000	80	3.0	7.4	100°	E26	5
L75DR56D3530K	LED 12W DR56 DIM 3000K	120V	12	75	70.8	850	3000K	35,000	80	3.0	7.4	100°	E26	5
L75DR56D3541K	LED 12W DR56 DIM 4100K	120V	12	75	70.8	850	4100K	35,000	80	3.0	7.4	100°	E26	5
L75DR56D3550K	LED 12W DR56 DIM 5000K	120V	12	75	70.8	850	5000K	35,000	80	3.0	7.4	100°	E26	5

## LED 120W Equivalent Options

### 16.5W DR56 Downlight • Dimmable • 35,000 Hour

L120DR56D3527K	LED 16.5W DR56 DIM 2700K	120V	16.5	120	84.8	1400	2700K	35,000	80	3.0	7.4	120°	E26	5
L120DR56D3530K	LED 16.5W DR56 DIM 3000K	120V	16.5	120	84.8	1400	3000K	35,000	80	3.0	7.4	120°	E26	5
L120DR56D3541K	LED 16.5W DR56 DIM 4100K	120V	16.5	120	84.8	1400	4100K	35,000	80	3.0	7.4	120°	E26	5
L120DR56D3550K	LED 16.5W DR56 DIM 5000K	120V	16.5	120	84.8	1400	5000K	35,000	80	3.0	7.4	120°	E26	5



**5 YEAR WARRANTY**  
\* Based on 12 hours use per day

For the most up-to-date specs, please visit [www.tcpi.com](http://www.tcpi.com)

TCP®

325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | [tcpi.com](http://tcpi.com)

©TCP DEC 2018/WF134836

