

TUNGSTEN HALOGEN LAMPS • BAYONET

JCV & JD

- Only for Use in Approved Enclosed Halogen Fixtures
- Double Contact Bayonet Base - BA15d
- Universal Burn Position
- 120 Volts (except as noted)

Watts (W)	Ordering Code	Lamp Description	Dimensions			Filament Type	Lumens (lm)	Color Temp (K)	Avg Life (h)	Bulb Finish	Case Qty	Fig No
			Dia (A)	MOL (B)	LCL (C)							
JCV – Double Contact Bayonet Base – BA15d												
75	1000986	JCV120V-75WGB	0.47	2.32	1.38	CC-8	1200	2800	1000	Clear	10	1
75	1000987	JCV120V-75WGBF	0.55	2.83	1.38	CC-8	1125	2850	1000	Frosted	10	1
100	1000968	JCV120V-100WGB	0.51	2.44	1.38	CC-8	1600	2800	2000	Clear	10	1
100	1000969	JCV120V-100WGBF	0.51	2.44	1.38	CC-8	1550	2800	2000	Frosted	10	1
100	1000364	ESR, JCV120V-100WGB2	0.51	2.44	1.38	CC-2V	1800	2850	750	Clear	10	2
100	1000374	ETD, JCV120V-100WGB2F	0.51	2.44	1.38	CC-2V	1750	2850	750	Frosted	10	2
150	1000373	ETC, JCV120V-150WGB	0.51	2.44	1.38	CC-8	2800	2900	2000	Clear	10	1
150	1000362	ESP, JCV120V-150WGB2	0.51	2.44	1.38	CC-2V	2800	2900	1000	Clear	10	2
150	1000376	ETF, JCV120V-150WGBF	0.51	2.44	1.38	CC-8	2700	2900	2000	Frosted	10	1
200	1000512	FEV, JCV120V-200WCB2	0.51	2.44	1.38	CC-2V	5500	3200	50	Clear	10	2
200	1001803	JCV230V-200WGB	0.60	2.48	1.38	CC-8	5000	2800	2000	Clear	20	1
250	1000365	ESS, JCV120V-250WGB	0.51	2.99	1.61	CC-8	5000	3000	2000	Clear	10	1
250	1000372	ETB, JCV120V-250WGBF	0.51	2.99	1.61	CC-8	4800	3000	2000	Frosted	10	1
250	1000990	JCV130V-250WGBF	0.51	2.99	1.61	CC-8	4800	3000	2000	Frosted	10	1
500	1000979	JCV120V-500WGB	0.51	3.43	2.13	CC-8	10450	2950	2000	Clear	10	1
500	1000980	JCV120V-500WGBF	0.51	3.43	2.13	CC-8	10100	2950	2000	Frosted	10	1
JD – Double Contact Bayonet Base – BA15d												
75	1003095	JD120V-75W/BA15D	0.53	2.56	1.26	CC-8	1125	2800	1000	Clear	10	3
75	1003638	JD120V-75W/BA15D	0.53	2.56	1.26	CC-8	1125	2800	1500	Clear	10	3
75	1003096	JD120V-75WF/BA15D	0.53	2.56	1.26	CC-8	1090	2800	1000	Frosted	10	3
100	1003097	JD120V-100W/BA15D	0.53	2.56	1.38	CC-8	1600	2800	1500	Clear	10	3
150	1003099	JD120V-150W/BA15D	0.53	2.56	1.38	CC-8	2800	2900	2000	Clear	10	3
150	1003100	JD120V-150WF/BA15D	0.53	2.56	1.38	CC-8	2700	2900	2000	Frosted	10	3

All dimensions shown in inches unless otherwise noted.

