



Ultra 8™ T8 Linear Fluorescent

T8 Linear Fluorescent Lamps

USHIO proudly carries a line of fluorescent lamps that include: standard Ultra 8™, Energy Saving and Extended Life T8 series of fluorescent lamps.

Through technological advances and the highest grade components, T8 fluorescent lamps can save up to 40% on energy costs with no loss of light over older technology T12 lamp types. The USHIO Ultra 8 T8 fluorescent series provides an economical as well as environmentally responsible alternative to standard T12 fluorescent lamps.

The Ultra 8 T8 lamps utilize protective coatings, effectively reducing the phosphor degradation while increasing lumen output. Advanced halophosphor and tri-phosphor coatings have been added to increase the lumen stability and allow higher loading.

(800 Series) Tri-Phosphor lamps render colors closer to that of nature. These lamps are most suitable for paint stores, retail shops, clothing boutiques, hair salons, printing businesses and graphic arts studios.

FEATURES & BENEFITS


- Select Lamps are TCLP Compliant - Low Mercury
Minimizes Effects of Lamp Disposal on the Environment
- Advanced Technology Saves Up to 40% on Energy Costs
Over T12 Lamps
- High Color Rendering - Up to 85 CRI
- Improved Light Distribution and Quality
- Environmental Asset - Long Life Prevents the Build Up of
Discarded Lamps Which Means Less Waste

APPLICATIONS

- Commercial & Retail Establishments
- Schools
- General Office
- Health Care Facilities

SPECIFICATIONS

Ultra 8™ T8 Linear Fluorescent



Sold in Case Quantity Only (25/Case)

Watts (W)	Ordering Code	Lamp Description	Dimensions			Color Temp (K)	Initial Lumens (lm)	Rated Life				
			Dia (A)	MOL (mm)	MOL (in)			IS ¹ (h)	RS/PRS ² (h)	IS ¹ (h)	RS/PRS ² (h)	
ULTRA 8™ T8 Tri-phosphor 800 Series³ — 85 CRI												
17	3000231	F17T8/830	1.0	610	24	3000	1400	24000*	30000**	30000*	36000**	
17	3000260	F17T8/835	1.0	610	24	3500	1400	24000*	30000**	30000*	36000**	
17	3000261	F17T8/841	1.0	610	24	4100	1400	24000*	30000**	30000*	36000**	
17	3000262	F17T8/850	1.0	610	24	5000	1350	24000*	30000**	30000*	36000**	
25	• 3000263	F25T8/830	1.0	915	36	3000	2250	24000*	30000**	30000*	36000**	
25	• 3000264	F25T8/835	1.0	915	36	3500	2250	24000*	30000**	30000*	36000**	
25	• 3000265	F25T8/841	1.0	915	36	4100	2250	24000*	30000**	30000*	36000**	
25	• 3000266	F25T8/850	1.0	915	36	5000	2150	24000*	30000**	30000*	36000**	
28	• 3000484	ⓔ F28T8/835	1.0	1219	48	3500	2800	24000*	30000**	40000*	42000**	
28	• 3000485	ⓔ F28T8/841	1.0	1219	48	4100	2800	24000*	30000**	40000*	42000**	
28	• 3000656	ⓔ F28T8/850	1.0	1219	48	5000	2725	24000*	30000**	40000*	42000**	
32	• 3000099	ⓔ F32T8/830	1.0	1219	48	3000	3050	24000*	30000**	40000*	42000**	
32	• 3000100	ⓔ F32T8/835	1.0	1219	48	3500	3050	24000*	30000**	40000*	42000**	
32	• 3000101	ⓔ F32T8/841	1.0	1219	48	4100	3050	24000*	30000**	40000*	42000**	
32	• 3000102	ⓔ F32T8/850	1.0	1219	48	5000	2950	24000*	30000**	40000*	42000**	
ULTRA 8™ T8 Tri-phosphor 800 Series High Lumen³ — 85 CRI												
32	3000480	ⓔ F32T8/841/HL	1.0	1219	48	4100	3150	24000*	30000**	40000*	42000**	
32	3000524	ⓔ F32T8/850/HL	1.0	1219	48	5000	3150	24000*	30000**	40000*	42000**	
ULTRA 8™ T8 Tri-phosphor 900 Series³ — 95 CRI												
32	3000417	ⓔ F32T8/960	1.0	1219	48	6000	2100	18000*	24000**	24000*	30000**	

* Based on ANSI / IESNA standards of 3 hours per start

**Based on estimated commercial operating standards of 12 hours per start

ⓔ = This bulb meets US Federal Minimum Efficiency Standard

• TCLP Compliant

¹ These life ratings are based on operation on instant start ballasts.

² These life ratings are based on operation on rapid start or programmed rapid start ballasts.

³ When using dimmers, dimming systems, or occupancy sensors, the lamp life will also be affected. The dimming system manufacturer can advise the affect of their system on lamp life.

(Hg) contains mercury
contient du mercure




Manage in Accord with Disposal Laws
www.lamprecycle.org 1-800-895-8842

25W & 28W Energy-Saving Ultra 8™ T8 Linear Fluorescent

USHIO is proud to introduce the newest additions to its popular Ultra 8™ T8 linear fluorescent lamp family. Energy costs account for the majority of lighting expenses and that illustrates the critical need for high performance and energy efficient lamp products. The Ultra 8 T8 lamps not only operate on high performance ballasts, they also provide the needed energy savings by directly replacing higher wattage 32W T8 lamps on Instant-Start ballast systems.* These tri-phosphor coated lamps provide the lumen stability and quality performance that goes hand-in-hand with dramatic energy savings (up to 22% energy savings vs. standard 32W Ultra 8 T8 lamps).

*This applies to F28T8ES only



G13



Sold in Case Quantity Only (25/Case)

Watts (W)	Ordering Code	Lamp Description	Dimensions			Color Temp (K)	Initial Lumens (lm)	Rated Life				Case Qty
			Dia (A)	MOL (mm)	MOL (in)			IS ¹ (h)	RS/PRS ² (h)	RS/PRS ² (h)	RS/PRS ² (h)	
ULTRA 8™ T8 Energy-Saving Tri-phosphor 800 Series³ — 85 CRI												
25	• 3000618	Ⓔ F25T8ES/835	1.0	1219	48	3500	2500	24000*	30000**	30000*	36000**	25
25	• 3000619	Ⓔ F25T8ES/841	1.0	1219	48	4100	2500	24000*	30000**	30000*	36000**	25
25	• 3000620	Ⓔ F25T8ES/850	1.0	1219	48	5000	2450	24000*	30000**	30000*	36000**	25
ULTRA 8™ T8 Energy-Saving Tri-phosphor 800 Series³ — 85 CRI												
28	• 3000621	Ⓔ F28T8ES/835	1.0	1219	48	3500	2800	24000*	30000**	30000*	36000**	25
28	• 3000622	Ⓔ F28T8ES/841	1.0	1219	48	4100	2800	24000*	30000**	30000*	36000**	25
28	• 3000623	Ⓔ F28T8ES/850	1.0	1219	48	5000	2700	24000*	30000**	30000*	36000**	25

* Based on ANSI / IESNA standards of 3 hours per start

**Based on estimated commercial operating standards of 12 hours per start







Ⓔ = This bulb meets US Federal Minimum Efficiency Standard

• TCLP Compliant

¹ These life ratings are based on operation on instant start ballasts.

² These life ratings are based on operation on rapid start or programmed rapid start ballasts.

³ When using dimmers, dimming systems, or occupancy sensors, the lamp life will also be affected. The dimming system manufacturer can advise the affect of their system on lamp life.



Ⓜ contains mercury
contient du mercure



Manage in Accord with Disposal Laws
www.lamprecycle.org 1-800-895-8842

SPECIFICATIONS


32W Extended Life Ultra 8™ T8 Linear Fluorescent



Extended Life F32T8 lamps offer an average rated life up to 60,000 hours* without sacrificing efficient light output or high color rendering. These lamps are an excellent solution for applications where frequency of lamp changes and cost of ownership are significant factors. Additionally, they reduce mercury use per lumen-hour, which is an important calculation for LEED Green Building Certification.

Available in multiple color temperatures: 3500K, 4100K and 5000K

*When used on programmed start ballasts at 12 hours per start.



Sold in Case Quantity Only (25/Case)

Watts (W)	Ordering Code	Lamp Description	Dimensions			Color Temp (K)	Initial Lumens (lm)	Rated Life				Case Qty
			Dia (A)	MOL (mm)	MOL (in)			IS ¹ (h)	RS/PRS ² (h)	RS/PRS ² (h)	RS/PRS ² (h)	
ULTRA 8™ T8 XL Extended Life Tri-phosphor 800 Series³ — 85 CRI												
32	3000612	Ⓔ F32T8XL/835, 48"	1.0	1219	48	3500	2950	36000*	40000**	55000*	60000**	25
32	3000611	Ⓔ F32T8XL/841, 48"	1.0	1219	48	4100	2950	36000*	40000**	55000*	60000**	25
32	3000610	Ⓔ F32T8XL/850, 48"	1.0	1219	48	5000	2875	36000*	40000**	55000*	60000**	25

* Based on ANSI / IESNA standards of 3 hours per start




Ⓔ = This bulb meets US Federal Minimum Efficiency Standard

**Based on estimated commercial operating standards of 12 hours per start

¹ These life ratings are based on operation on instant start ballasts.

² These life ratings are based on operation on rapid start or programmed rapid start ballasts.

³ When using dimmers, dimming systems, or occupancy sensors, the lamp life will also be affected. The dimming system manufacturer can advise the affect of their system on lamp life.



Ⓔ contains mercury
contient du mercure



Manage in Accord with Disposal Laws
www.lamprecycle.org 1-800-895-8842