



LED Selectable Recessed Downlight

Product Specifications

Color & Wattage Selectable



For quick, easy, and affordable LED upgrades, switch to TCP's LED Downlights. TCP downlights have quick snap holding arms to quickly attach to a recessed can. With this classic look, these downlights provide smooth even light in the color temperature you need.

Reasons to choose the LED Selectable Recessed Downlights from TCP

- Select between 2400K, 2700K, 3000K or, 3000K, 4000K, 5000K
- Product also allows for wattage selectivity
- Long, 50,000 hour life minimizes replacement and maintenance costs
- Very low heat generation makes the downlight perfect for sensitive display lighting
- Mounts directly to a 5" or 6" recessed can for easy installation
- Smooth, uniform dimming from 100 - 5%
- Excellent color consistency and CRI enhances colors of the focal point while maintaining uniformity throughout lighting installation

Ideal Applications

- Commercial
- Industrial
- Retail
- Residential
- Healthcare

Specifications:

Color Temperatures 2400K, 2700K, 3000K or
3000K, 4000K, and 5000K
 Wattage Options 8W, 10.5W, 14.5W
 Input Line Voltage 120 VAC
 Input Line Frequency..... 50/60HZ
 Lamp Life (Rated) 50,000 hours

Minimum Starting Temp -22°F/-30°C
 Maximum Operating Temp..... 104°F/40°C
 CRI..... 80
 IC-rated for direct contact with insulation
 UL approved for damp location (indoor only)—outdoor environment may cause yellowing of the white trim. This is not covered by warranty.



Specifications:



5\"/>

ITEM #	DESCRIPTION	VOLTAGE	WATTS	INCANDES. WATTS	LPW			LUMENS			COLOR	CRI	ENERGY STAR RATED	MOL (inches)	DIA (inches)	BEAM ANGLE
					8 WATTS	10.5 WATTS	14.5 WATTS	8 WATTS	10.5 WATTS	14.5 WATTS						
LED 120W Equivalent Options																
DR56 Downlight • E26 Base • Dimmable • 50,000 Hour																
LEDWSDR56CCT1	5\"/>	120V	8/ 10.5/ 14.5	120	95.6/ 106.3/ 106.3	95.3/ 104.8/ 104.8	86.9/ 96.6/ 96.6	765/ 850/ 850	1000/ 1100/ 1100	1260/ 1400/ 1400	2400K/ 2700K/ 3000K	80		3.0	7.4	90°
LEDWSDR56CCT2	5\"/>	120V	8/ 10.5/ 14.5	120	106.3/ 106.3/ 106.3	104.8/ 104.8/ 104.8	96.6/ 96.6/ 96.6	850/ 850/ 850	1100/ 1100/ 1100	1400/ 1400/ 1400	3000K/ 4000K/ 5000K	80	★	3.0	7.4	90°

TCP Standard LED Lamps, LED Filament Lamps and TCP Downlights have been tested to work with the following dimmers:

BRAND	MODEL
LUTRON	AYCL-153P
	CTCL-153PD-H
	CTCL-53PD-H
	DV-600P
	DV-600PR-WH
	DV-603PH-WH
	DVCL-153P
	LGCL-153P
	MACL_153M
	MSCLOP153M
	PD-6WCL
	SCL-153PR
	SELV-300P
	TGCL-153P
MRF2S-6ELV120-WH	
LEVITON	6811
	6602
	6631
	6672
	6672-L
	6674
	DSL06
	IPL06
COOPER	DAL06P
	SAL06P

*Dimming compatibility tests are performed under a controlled lab environment. Field conditions may vary from this type of environment. Dimmers may differ by age and versions under the same item number which may affect compatibility. Compatibility may also extend beyond this list as TCP products should work with most C-L Type Triac Dimmers. TCP recommends trying a few dimmer-lamp combinations in an on-site test to ensure compatibility and performance before a major installation. If there's a dimmer not on this list we can perform a lab test for compatibility.

TECHNOLOGY CAST IN A BEAUTIFUL LIGHT

For over 20 years, TCP has been designing, developing and delivering energy-efficient lighting into the market. Thanks to our cutting-edge technology and manufacturing expertise, we have shipped billions of high quality lighting products. With TCP, you can count on a lighting product that is designed to meet the needs of the market - that transforms your surroundings and envelopes you in warmth - lighting that generates beauty with every flip of the switch.

Sales:

Date:

Model:

Project:

Rep:

Catalog Number:

Type:

Notes:



For more information on the quality and care TCP can deliver, call us at **800.324.1496** or visit tcp.com

325 Campus Dr. | Aurora, Ohio 44202 | P: 800.324.1496 | F: 877.487.0516