

Applications

TCP custom screen printing allows for creative DT series panel designs. Any high-resolution image can be applied to turn a typical DT series panel into a marketing piece, sky image like shown, and more.

Specifications

Input Line Voltage	120-277 VAC
Input Line Frequency (Hz)	50/60HZ
Wattage (W)	
2'x2'	23W/29W/38W
2'x4'	29W/39W/46W
Lumens (l)	
2'x2'	2600L/3200L/4200L
2'x4'	3300L/4400L/5100L
Rated Life	50,000 hours
Minimum Starting Temperature	-20°C
Maximum Operating Temperature	40°C
Power Factor	>90%
THD	<20%
Ratings	UL/cUL damp location rated, IC rated, IP20
Controls	0-10V dimming (standard)

2'x2'



2'x4'



Catalog Ordering Matrix				
Example: DT2UZDCLOUD				
DT		U	ZD	CLOUD
FAMILY	SIZE	VOLTAGE	DIMMING	LENS TYPE
DT = Direct Back-Lit Troffer	2 = 2' x 2' 4 = 2' x 4'	U = 120V-277V	ZD = 0-10V Dimming	CLOUD

TECHNOLOGY CAST IN A BEAUTIFUL LIGHT

For over 20 years, TCP has been designing, developing and delivering energy-efficient lighting into the market. Thanks to our cutting-edge technology and manufacturing expertise, we have shipped billions of high quality lighting products. With TCP, you can count on a lighting product that is designed to meet the needs of the market - that transforms your surroundings and envelopes you in warmth - lighting that generates beauty with every flip of the switch.

Sales:

Date:

Model:

Project:

Rep:

Catalog Number:

Type:

Notes:



For more information on the quality and care TCP can deliver, call us at **800.324.1496** or visit tcpi.com

325 Campus Dr. | Aurora, Ohio 44202 | P: 800.324.1496 | F: 877.487.0516